



value

Sun Blade™ 150 Workstation

THE PRICE LEADER IN 64-BIT UNIX® WORKSTATIONS

SUN BLADE™ 150 WORKSTATION SPECIFICATIONS

For technical and business computing environments looking to balance advanced 64-bit capabilities, workstation performance, support for the Solaris™ Operating Environment and cost considerations, Sun has the ideal solution: the Sun Blade™ 150 workstation. This powerful, low-cost system boasts a full 64-bit architecture with the latest high-performance UltraSPARC® III CPU, supporting up to 2 GB of memory and up to 80 GB of internal storage. Features such as a fast PCI bus and the latest I/O technologies including USB and IEEE-1394 provide connectivity to a wide variety of latest generation peripherals. And with graphics options that include the high resolution on-board Sun PGX64™ 2D graphics or high-end Sun™ XVR-500 3D graphics, the Sun Blade 150 workstation delivers advanced workstation capabilities with exceptional performance at an affordable price. With only a 20% increase in megahertz, the doubling of the cache to 512 KB plus the new Sun XVR-500 graphics, the Sun Blade 150 workstation cranks up the performance. It's up to 63% faster on compute-intensive applications and up to 76% faster in MCAD applications*.

PROCESSOR	
550 MHz or 650 MHz UltraSPARC III: 512 KB L2 on-die cache	
MEMORY	
2 GB maximum, error correction SDRAM	
Four DIMM slots, PC133 168-pin DIMMs (128 MB, 256 MB, and 512 MB DIMMs)	

STANDARD INTERFACES	
Network	Ethernet/Fast Ethernet, twisted pair standard (10-BaseT and 100-BaseT)
Serial	One D-Sub 9-pin connector, asynchronous, two IEEE 1394a, four USB 1.1
Parallel	One D-Sub 25-pin connector, IEEE 1284
Audio I/O	Four audio ports: line-in/line-out/micro phone-in/speaker-out
Expansion bus	Three 32-bit PCI slots, full-size, 33 MHz, 5 V (3.3 V power supplied)

MASS STORAGE AND MEDIA	
Internal disk	Up to 40 GB, 7200-rpm Enhanced IDE disk drive
Internal CD-ROM	48x-speed CD-ROM or 16X-speed DVD-ROM
Internal floppy disk	One 3.5-in., 1.44-MB floppy
Expansion	2nd disk drive bay available

GRAPHICS AND IMAGING	
On-board 24-bit Sun PGX64 2D graphics and optional Sun PGX64 or Sun XVR-500 3D graphics boards	
Up to 3 PGX64 2D graphics boards or 2 Sun XVR-500 3D graphics boards supported	

Sun PGX64 graphics			
Resolution	Refresh Rate	Standard	Aspect Ratio
1920 x 1200	70 Hz	Sun	16:10
1920 x 1080	72 Hz	Sun	16:9
1600 x 1280	76 Hz	Sun	5:4
1600 x 1000	66, 76 Hz	Sun	16:10
1280 x 1024	67, 76 Hz	Sun	5:4
1280 x 1024	75 Hz	VESA	5:4
1152 x 900	66, 76 Hz	Sun	5:4
1024 x 768	60, 70, 85 Hz	Sun	4:3
1024 x 768	75 Hz	VESA	4:3
800 x 600	56, 60, 72 Hz	Sun	4:3
720 x 400	70, 85 Hz	Sun	Portrait
640 x 480	60, 72 Hz	Sun	4:3
640 x 480	75 Hz	VESA	4:3

Sun XVR-500 graphics			
Resolution	Refresh Rate	Standard	Aspect Ratio
1920 x 1080	72 Hz	Sun	16:9
1600 x 1280	76 Hz	Sun	5:4
1600 x 1200	75 Hz	VESA	4:3
1600 x 1000	66, 76 Hz	Sun	16:10
1440 x 900	76 Hz	Sun	16:10
1280 x 800	112 Hz	Sun-Stereo	16:10
1280 x 800	76 Hz	Sun	16:10
1280 x 1024	60, 75, 85 Hz	VESA	5:4
1280 x 1024	67, 76 Hz	Sun	5:4
1152 x 900	120 Hz	Sun-Stereo	5:4
1152 x 900	66, 76 Hz	Sun	5:4
1024 x 800	84 Hz	Sun	5:4
1024 x 768	60, 70, 77 Hz	Sun	4:3
960 x 680	108, 112 Hz	Sun-Stereo	Sun-Stereo
768 x 575	50i Hz	PAL	PAL
640 x 480	60 Hz	VESA	4:3
640 x 480	60i Hz	NTSC	NTSC

SOFTWARE	
Operating System	Solaris 8 Operating Environment (02/02) pre-installed, Solaris 9 Operating Environment supported

MONITOR OPTIONS	
17-inch entry color	Up to 1024 x 786 resolution, 76 Hz refresh rate
18.1-inch flat panel	Up to 1280 x 1024 resolution, 76 or 66 Hz refresh rate
21-inch color	Up to 1600 x 1200 resolution, 75 Hz refresh rate
24.1-inch LCD	Up to 1920 x 1200 resolution, 60 Hz refresh rate

PC INTEROPERABILITY	
Optional SunPCI[tm] IIpro coprocessor card allows you to run several operating systems on your system simultaneously (Windows and Solaris), providing you the best of both worlds.	

ENVIRONMENT	
AC power	100, 120; 220-240 VAC, 47-63 Hz, 0.35 kVA (max. continuous), 5.0 A (surge)
Operating	5°C to 35°C (40° F to 95° F), IEC 60068-2-1, IEC 60068-2-2 Test Bd 10% to 90% relative humidity, noncondensing, 27° C maximum web bulb

Nonoperating	-40° C to 65° C (4° F to 150° F), IEC 60068-2-1, IEC 60068-2-2 Test Bd up to 93% relative humidity, noncondensing, 38° C maximum wet bulb
---------------------	---

Operating acoustic noise	5.5 bels
Idling acoustic noise	4.8 bels

REGULATIONS	
Meets or exceeds the following requirements:	
Safety	UL /CSA-60950, EN60950, IEC950 CB Scheme with all country deviations, IEC825-1, 2 and CFR21 part 1040

Ergonomics	EK1-ITB-2000
RFI/EMC	EN55022/CISPR22 Class B, FCC CFR47 Part 15 Class B, EN61000-3-2, EN61000-3-3

Immunity	EN 55024
X-ray (for Monitors)	DHHS 21 Subchapter J; PTB German X-ray Degree

Regulatory markings	CE, FCC, ICES-003, C-tick, VCCI, GOST-R, BSMI, EK, UL/cUL, TUV-GS, E-Star
----------------------------	---

Power management	Energy Star compliant on all standard configurations
-------------------------	--

DIMENSIONS AND WEIGHT	
Height	117 mm (4.6 in.)
Width	457 mm (18.0 in.)
Depth	446 mm (17.6 in.)
Shipping weight	12.2 kg (26.9 lb.)

HEADQUARTERS SUN MICROSYSTEMS, INC., 4150 NETWORK CIRCLE, SANTA CLARA, CA 95054 USA
 PHONE: 650 960-1300 OR 800 555-9SUN INTERNET: www.sun.com

SALES OFFICES

AFRICA (NORTH, WEST AND CENTRAL): +9714-3366333 • ARGENTINA: +5411-4317-5600 • AUSTRALIA: +61-2-9844-5000 • AUSTRIA: +43-1-60563-0 • BELGIUM: +32-2-704-8000 • BRAZIL: +55-11-5187-2100 • CANADA: +905-477-6745 • CHILE: +56-2-3724500 • COLOMBIA: +571-629-2323 • COMMONWEALTH OF INDEPENDENT STATES: +7-502-935-8411
 CZECH REPUBLIC: +420-2-3300-9311 • DENMARK: +45 4556 5000 • EGYPT: +202-570-9442 • ESTONIA: +372-6-308-900 • FINLAND: +358-9-525-561 • FRANCE: +33-134-03-00-00 • GERMANY: +49-89-46008-0 • GREECE: +30-1-618-8111 • HUNGARY: +36-1-489-8900 • ICELAND: +354-563-3010 • INDIA: BANGALORE: +91-80-2298989/2295454; NEW DELHI: +91-11-6106000; MUMBAI: +91-22-2018141 • IRELAND: +353-1-8055-666 • ISRAEL: +972-9-9710500 • ITALY: +39-039-60551 • JAPAN: +81-3-5717-5000 • KAZAKHSTAN: +7-3272-466774 • KOREA: +82-2193-5114 LATVIA: +371-750-3700 • LITHUANIA: +370-729-8468 • LUXEMBOURG: +352-49 11 33 1 • MALAYSIA: +603-21161888
 MEXICO: +52-5-258-6100 • THE NETHERLANDS: +00-31-33-45-15-000 • NEW ZEALAND: AUCKLAND: +64-9-976-6800; WELLINGTON: +64-4-462-0780 • NORWAY: +47 23 36 96 00 • PEOPLE'S REPUBLIC OF CHINA: BEIJING: +86-10-6803-5588; CHENGDU: +86-28-619-9333; GUANGZHOU: +86-20-8755-5900; SHANGHAI: +86-21-6466-1228; HONG KONG: +852-2202-6688 • POLAND: +48-22-8747800 • PORTUGAL: +351-21-4134000 • RUSSIA: +7-502-935-8411 • SINGAPORE: +65-438-1888 • SLOVAK REPUBLIC: +421-2-4342-94-85 • SOUTH AFRICA: +2711-805-4305 • SPAIN: +34-91-596-9900 • SWEDEN: +46-8-631-10-00 • SWITZERLAND: GERMAN: 41-1-908-90-00; FRENCH: 41-22-999-0444 • TAIWAN: +886-2-8732-9933 • THAILAND: +662-344-6888 • TURKEY: +90-212-335-22-00 • UNITED ARAB EMIRATES: +9714-3366333 • UNITED KINGDOM: +44-1-276-20444 • UNITED STATES: +1-800-555-9SUN OR +1-650-960-1300 • VENEZUELA: +58-2-905-3800 • OR ONLINE AT SUN.COM/STORE

SUN™ Specifications are subject to change without notice. © 2002 Sun Microsystems, Inc. All rights reserved. Sun, Sun Microsystems, the Sun logo, Solaris, Sun Blade and Sun PGX64, are trademarks or registered trademarks of Sun Microsystems, Inc., in the United States and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc., in the United States and other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc. LFC1.2 Printed in USA 8/02

* Performance compared to Sun Blade™ 100 workstation with Sun™ Expert3D-Lite graphics running ABAQUS v6.2 and Unigraphics v18 applications.

